

**WHAT IS CLAIMED IS:**

Claims 1-27 (Cancelled).

28. (Previously Presented) An electrical power transmission line, comprising:  
at least one electrical cable;  
a conduit of ferromagnetic material enclosing said at least one cable and  
comprising a base and a cover; and  
electrical contact elements electrically connecting said base and said  
cover, wherein said electrical contact elements are selected from the group of  
metal fusion joints and resilient members suitable to penetrate said ferromagnetic  
material.
29. (Previously Presented) The electrical power transmission line of claim 28,  
wherein said base and said cover have superimposed portions on both sides of  
said conduit, and wherein said electrical contact elements are applied to said  
superimposed portions.
30. (Previously Presented) The electrical power transmission line of claim  
28, wherein said resilient members are clips provided with portions able to  
penetrate said ferromagnetic material.
31. (Previously Presented) The electrical power transmission line of claim 29,  
wherein said superimposed portions are separated by an air gap and said  
superimposed portions have a width that is at least five times greater than the  
thickness of said air gap.

32. (Previously Presented) The electrical power transmission line of claim 31, wherein said air gap is at most 3% of the perimeter of the cross section of said conduit.
33. (Previously Presented) The electrical power transmission line of claim 28, wherein the electrical contact elements have a reciprocal longitudinal distance of at most 50 cm.
34. (Previously Presented) The electrical power transmission line of claim 33, wherein said reciprocal longitudinal distance is at most 25 cm.
35. (Previously Presented) The electrical power transmission line of claim 28, wherein the conduit comprises a plurality of longitudinal sections partially superimposed on each other and each comprising a base portion and a cover portion.
36. (Previously Presented) The electrical power transmission line of claim 35, wherein said longitudinal sections are electrically coupled to each other.
37. (Previously Presented) The electrical power transmission line of claim 35, wherein the cover portion and the base portion of each of said longitudinal sections are longitudinally shifted from each other.
38. (Previously Presented) The electrical power transmission line of claim 35, wherein said longitudinal sections are superimposed of a length that is at least 25% of the width of said conduit.
39. (Previously Presented) The electrical power transmission line of claim 28, wherein said ferromagnetic material is steel.

40. (Previously Presented) The electrical power transmission line of claim 28, wherein said at least one cable comprises three cables arranged in a trefoil configuration.

41. (Previously Presented) The electrical power transmission line of claim 35, wherein at least two of said longitudinal sections extend along different directions, wherein said conduit comprises a joining member for joining said two conduit sections, and wherein said joining member consists of two parts electrically connected by means of said electrical contact elements.

42. (Previously Presented) The electrical power transmission line of claim 35, wherein said base portion has a "U"-shaped cross-section.

43. (Previously Presented) The electrical power transmission line of claim 28, wherein said cover portion is substantially flat.

44. (Previously Presented) The electrical power transmission line of claim 28, wherein the conduit is placed underground.

45. (Previously Presented) The electrical power transmission line of claim 29, wherein a material having a magnetic permeability greater than air is positioned between said superimposed portions of said base and said cover.

46. (Previously Presented) A method for screening the magnetic field generated by an electrical power transmission line comprising at least one electrical cable, said method comprising the steps of:

placing said electrical cable in a conduit of ferromagnetic material comprising a base and a cover; and

providing an electrical connection between said base and said cover  
having a conductance, per meter of length, of at least 150 Siemens/m.

47. (Previously Presented) The method of claim 46, wherein said  
conductance is at least 500 Siemens /m.

48. (Previously Presented) The method of claim 47, wherein said  
conductance is at least 1500 Siemens/m.

49. (Previously Presented) The method of claim 46, wherein providing an  
electrical connection between said base and said cover comprises elastically  
coupling said base and said cover with material interpenetration.

50. (Previously Presented) The method of claim 46, wherein providing an  
electrical connection between said base and said cover comprises realizing a  
metal fusion between said base and said cover.

51. (Previously Presented) The method of claim 46, wherein placing said  
electrical cable in a conduit comprises superimposing respective lateral portions  
of said base and said cover, and wherein providing an electrical connection  
between said base and said cover comprises electrically coupling said lateral  
portions.

52. (Previously Presented) The method of claim 51, wherein electrically  
coupling said lateral portions comprises applying to said lateral portions a  
plurality of metal resilient clips able to pierce the surface of said lateral portions  
under their elastic action.

53. (Previously Presented) The method of claim 46, wherein placing said  
electrical cable in a conduit comprises arranging the base underground, laying

down said at least one cable into said base, and leaning the cover onto said base so as to substantially close said conduit.

54. (Previously Presented) The method of claim 46, wherein the conduit comprises a plurality of longitudinal sections and the method comprises electrically coupling said longitudinal sections to each other.